

0390203307

AHC2 Two-stage motor with Transmission



For reliable performance in reduced size: The Bosch compact geared motors are the appropriate solution for industrial applications with limited space. These drives exhibit high power density and cover a broad field of 12 and 24V requirements. Bosch offers different speed/torque characteristic curves and various mechanical interfaces.

Degree of protection: IP 50

Operating mode: S2

Rotation direction: Left and right

rotation

Nominal voltage: 12 V

-100










Contact us!

Product Specification

Technical data and performance curve



Nominal power (W): 3,9

Nominal current (A): 3,7

Nominal speed (rpm): 18,65

Nominal torque (Nm): 2

Stall torque (Nm): 23,9

Transmission ratio: 217:1


Hall Sensor: No

Transmission position: Left






Dimensions




Please contact us if you need a 3d model

Contact

Circuit diagram



Connector



Housing:

TE 968182-1

Locker:

TE 968183-1


PIN:

TE JPT 0-927768-1

ming io



Drive interface



Features and benefits

- Rotation in both direction: The Bosch small geared motors can be used as a drive
- Available with hall sensor: For positioning or direction of rotation feedback
- Production in line with the original automotive quality guidelines: For proven quality, high reliability and a long service life
- Operating mode S2 or S3: Suitable for short-term or intermittent operation

Downloads

You may also be interested in:

To Product family: Catalogue

